



# BLACK Ultra

### Quattro High-Gain Low-Noise 40mm LNB

#### IDLB-QUTL40-ULTRA-OPP

This LNB is a high performance product featuring the lowest noise figure available to address the need for superior reception under the edges of the satellite footprint skirt. Thanks to its novel front-end architecture and superior components, this LNB provides higher conversion gain yet with lowest noise figure and best phase noise performance. The combination of higher spec components, excellent isolation and advanced filter design enables improved handling of interfering spurious and provides the leap in the overall reception performance compared with standard LNBs. This LNB enables the reception of signal from one satellite and its distribution via a multi-switch to numerous Set-top boxes and is ready for High Definition transmissions. Manufactured to the highest industry quality standards and designed to meet strict specifications, this LNB is an ideal solution for the satellite broadcast reception across Europe.

#### Main Features

- Superior Phase Noise performance DVB-S2 (HDTV) compliant
- Excellent isolation extremely high cross-pol performance
- Very low spurious levels
- Superior Noise Figure
- Higher conversion gain
- Ultimate reliability

#### High-Gain Low-Noise

## **Technical Specifications**



Low Band Input Frequency Range	10.7~11.7 GHz
Low Band Output Frequency Range	950~1950 MHz
LO Frequency	9.75 GHz
High Band Input Frequency Range	11.7~12.75 GHz
High Band Output Frequency Range	1100~2150 MHz
LO Frequency	10.6 GHz
Noise Figure	0.2dB typ. (0.7dB max.)
LO Initial Accuracy	+/- 1.0 MHz max.
LO Temperature Drift	+/- 3.0 MHz max.
LO Phase Noise @ 10K Hz	-90 dBc/Hz max.
Conversion Gain	60 dB min.
Gain Ripple	+/- 0.75 dB/27MHz
Gain Variation	+/- 4 dB
Image Rejection	40 dB min.
1 dB Compression Point (O/P)	0.0 dBm min.
Cross talk	23dB min.
Output VSWR	2.0 : 1
Radiated Interference	-60 dBm max.
DC Power	200mA max. @ 11 – 20V
Working Temperature	-30~+60 °C
Output Impedance (connect to STB)	75Ω
Output connector	F-type (female)
Weight	344 g





For purpose of brevity, some product descriptions in this sheet remain at platform level and may not be referred to as detailed datasheets of the products. Inverto Digital Labs reserves the right to amend, omit or add products, product-lines, and/ or features without notice.

FTA communication Technologies Tel. +352 264 367 1 Fax. +352 264 313 68

www.inverto.tv Sales@inverto.tv STBsupport@inverto.tv